

IN THE CLAIMS:

1. (currently amended) A data processing system comprising:
 - a memory for storing operands;
 - at least one general purpose register, wherein the memory does not include the at least one general purpose register; and
 - processor circuitry for executing one or more instructions, at least one of the one or more instructions for transferring data elements between the memory and the at least one general purpose register wherein one of the one or more instructions specifies: (a) a first offset between data elements within a first portion of successive data elements in the memory; (b) a first number of data elements to be transferred between the memory and the at least one GPR; and (c) a second offset between the first portion and a second portion of data elements in the memory.
2. (original) The data processing system of claim 1 wherein the one of the one or more instructions further specifies a data element size of the data elements in the memory.
3. (original) The data processing system of claim 1 wherein the one of the one or more instructions further specifies size of data elements in the memory separate and independent from specifying size of data elements in the at least one general purpose register.
4. (original) The data processing system of claim 3 wherein the processor circuitry determines a total number of data elements to be transferred based on size of data elements in the memory.
- 5 (original) The data processing system of claim 3 wherein the processor circuitry determines a total number of data elements to be transferred based on size of data elements in the at least one general purpose register.
6. (original) The data processing system of claim 1 wherein the one of the one or more instructions further specifies a total number of data elements to be transferred between the memory and the at least one general purpose register.

7. (original) The data processing system of claim 1 wherein the data processing system further comprises a first general purpose register and a second general purpose register wherein the one of the one or more instructions transfers data elements between the memory and both the first general purpose register and the second general purpose registers in response to executing the one of the one or more instructions.
8. (original) The data processing system of claim 7 wherein the one of the one or more instructions further specifies a total number of data elements to be transferred between the memory and both the first general purpose register and the second general purpose register.
9. (original) The data processing system of claim 8 wherein if the total number of data elements transferred does not completely fill the second general purpose register, the processor circuitry fills at least a portion of any remaining bit locations with a predetermined value.
10. (original) The data processing system of claim 7 wherein the one of the one or more instructions further separately specifies a number of data elements to be transferred between the memory and each of the first and second general purpose registers.
11. (original) The data processing system of claim 7 wherein if the total number of data elements transferred does not completely fill the second general purpose register, the processor circuitry fills at least a portion of any remaining bit locations with a predetermined value.
12. (original) The data processing system of claim 1 wherein the one of the one or more instructions further comprises a specifier wherein the second offset is used no more than once by the processor circuitry while transferring the first number of data elements.
13. (original) The data processing system of claim 12 wherein the processor circuitry communicates data elements in the memory by using a circular buffer when the one of the one or more instructions specifies that the second offset is to be used only once.
14. (original) The data processing system of claim 1 wherein the one of the one or more instructions further comprises a specifier wherein the second offset is used more than once by the processor circuitry if the first number of data elements to be transferred is larger than twice the first portion of data elements to be transferred.

15. (original) A data processing system comprising:
a memory for storing operands;
at least one general purpose register; and
processor circuitry for executing one or more instructions, at least one of the one or more instructions for transferring data elements between the memory and the at least one general purpose register wherein one of the one or more instructions specifies a radix specifier for implementing transferring one or more data elements in a bit-reversed order between the memory and the at least one general purpose register.
16. (currently amended) A method for using multiple addressing modes comprising:
providing a memory for storing operands;
providing at least one general purpose register, wherein the memory does not include the at least one general purpose register;
executing one or more instructions, at least one of the one or more instructions transferring data elements between the memory and the at least one general purpose register;
specifying with the at least one of the one or more instructions a first offset between data elements within a first portion of successive data elements in the memory;
specifying with the at least one of the one or more instructions a first number of data elements to be transferred between the memory and the at least one GPR; and
specifying with the at least one of the one or more instructions a second offset between the first portion and a second portion of data elements in the memory.
17. (original) The method of claim 16 further comprising:
using the at least one of the one or more instructions to further specify a data element size of the data elements in the memory.

18. (original) The method of claim 16 further comprising:
using the at least one of the one or more instructions to further specify size of data elements in the memory separate and independent from specifying size of data elements in the at least one general purpose register.
19. (original) The method of claim 16 further comprising using a processor to determine a total number of data elements to be transferred based on size of data elements in the memory.
20. (original) The method of claim 19 further comprising using the processor to determine a total number of data elements to be transferred based on size of data elements in the at least one general purpose register.
21. (original) The method of claim 16 further comprising using the at least one instruction of the one or more instructions to further specify a total number of data elements to be transferred between the memory and the at least one general purpose register.
22. (original) The method of claim 16 further comprising providing a first general purpose register and a second general purpose register and transferring data elements between the memory and both the first general purpose register and the second general purpose registers in response to executing the one of the one or more instructions.
23. (original) The method of claim 22 further comprising using the one of the one or more instructions to further specify a total number of data elements to be transferred between the memory and both the first general purpose register and the second general purpose register.
24. (original) The method of claim 22 further comprising filling at least a portion of any remaining unfilled bit locations in the second general purpose register with a predetermined value if a total number of data elements transferred does not completely fill the second general purpose register.
25. (original) The method of claim 21 further comprising using the one of the one or more instructions to further separately specify a number of data elements to be transferred between the memory and each of the first and second general purpose registers.

26. (original) The method of claim 21 wherein if the total number of data elements transferred does not completely fill the second general purpose register, filling at least a portion of any remaining bit locations with a predetermined value.
27. (original) The method of claim 16 further comprising providing a specifier in the one of the one or more instructions wherein in response to the specifier, the second offset is used only once by a processor transferring the first number of data elements.
28. (original) The method of claim 27 further comprising communicating data elements in the memory under control of the processor by using a circular buffer when the one of the one or more instructions specifies that the second offset is to be used only once.
29. (original) The method of claim 16 further comprising providing a specifier in the one of the one or more instructions wherein in response to the specifier, the second offset is used more than once by a processor if the first number of data elements to be transferred is larger than twice the number of data elements in the first portion of data elements in the memory.
30. (original) The data processing system of claim 16 further comprising providing a radix specifier in the one of the one or more instructions, the radix specifier implementing transfer of one or more data elements in a bit-reversed order between the memory and the at least one general purpose register.
31. (currently amended) A data processing addressing method comprising:
 providing a memory for storing operands;
 providing at least one general purpose register;
 executing one or more instructions, at least one of the one or more instructions
 transferring data elements between the memory and the at least one
 general purpose register;
 specifying with the ~~at least~~ one of the one or more instructions a radix specifier in
 the one of the one or more instructions, the radix specifier implementing
 transfer of one or more data elements in a bit-reversed order between the
 memory and the at least one general purpose register.

32. (original) A data processing system addressing method comprising:
- providing a memory for storing operands;
 - providing at least one general purpose register; and
 - providing processor circuitry for executing one or more instructions, at least one of the one or more instructions for transferring data elements between the memory and the at least one general purpose register wherein one of the one or more instructions implements storing predetermined data elements in the memory in a bit-reversed order and transferring the predetermined data elements into the at least one general purpose register.
33. (original) The method of claim 32 wherein the at least one of the one or more instructions further specifies a number of data elements to transfer into the at least one general purpose register.
34. (original) The method of claim 32 wherein the at least one of the one or more instructions further specifies size of data elements in the memory separate and independent from specifying size of data elements in the at least one general purpose register.
35. (original) A data processing system addressing method comprising:
- providing a memory for storing operands;
 - providing at least one general purpose register; and
 - providing processor circuitry for executing one or more instructions, at least one of the one or more instructions for transferring data elements between the memory and the at least one general purpose register wherein one of the one or more instructions stores predetermined data elements in the memory in a sequential order and transferring the predetermined data elements into the at least one general purpose register in a bit-reversed order.
36. (original) The method of claim 35 wherein the at least one of the one or more instructions further specifies a number of data elements to transfer into the at least one general purpose register.

37. (original) The method of claim 35 wherein the at least one of the one or more instructions further specifies size of data elements in the memory separate and independent from specifying size of data elements in the at least one general purpose register.

38. (original) A data processing system addressing method comprising:

- providing a memory for storing operands;
- providing at least one general purpose register; and
- providing processor circuitry for executing one or more instructions, at least one of the one or more instructions for transferring data elements between the memory and the at least one general purpose register wherein one of the one or more instructions implements storing predetermined data elements in the at least one general purpose register in a bit-reversed order and transferring the predetermined data elements into the memory.

39. (original) The method of claim 38 wherein the at least one of the one or more instructions further specifies a number of data elements to transfer into the memory.

40. (original) The method of claim 38 wherein the at least one of the one or more instructions further specifies size of data elements in the memory separate and independent from specifying size of data elements in the at least one general purpose register.

41. (original) A data processing system addressing method comprising:

- providing a memory for storing operands;
- providing at least one general purpose register; and
- providing processor circuitry for executing one or more instructions, at least one of the one or more instructions for transferring data elements between the memory and the at least one general purpose register wherein one of the one or more instructions stores predetermined data elements in the at least one general purpose register in a sequential order and transferring the predetermined data elements into the memory in a bit-reversed order.

42. (original) The method of claim 40 wherein the at least one of the one or more instructions further specifies a number of data elements to transfer into the memory.

43. (original) The method of claim 40 wherein the at least one of the one or more instructions further specifies size of data elements in the memory separate and independent from specifying size of data elements in the at least one general purpose register.